



**IMSA TECHNICAL BULLETIN IWSC #21-32**

To: All IMSA WeatherTech SportsCar Competitors  
From: IMSA Competition  
Date: September 17, 2021  
Re: IMSA ACURA Grand Prix of Long Beach Balance of Performance Tables

---

In accordance with Attachment 2 of the IMSA WeatherTech SportsCar SSR, the following road-course Balance of Performance values are set for the indicated Car Models. The column listed as current is the current specification after any adjustment is applied and thus the required specification for the Event. These decisions come into immediate effect and are applicable until further notice.



One Daytona Blvd.  
Daytona Beach, FL  
32114  
+1 (386) 310-6500



DPI	Vehicles		Mass		Engine						Aero	Fuel				Notes			
	Manufacturer		Minimum No Fuel/Driver (kg)		Make	Volume (L)	Turbo/NA	Restrictor Diameter (mm)			Average Power Delta (kW)	Maximum RPM	Configuration	Type	Declared Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)	
			adj	current				qty.	adj	current	adj					current	λ		
Acura	ARX-05		930	Acura	3.5	Turbo					7050	See Table	E20	0.89		77.0	30.0		
Cadillac	DPI-V.R		945	Cadillac	5.5	NA	2		32.2		7600	See Table	E20	0.90		72.0	30.0		
Mazda	RT24-P		920	Mazda	2.0	Turbo					9300	See Table	E20	0.85		83.0	30.0		

\* Aero configuration is defined via the Aero Configuration table on the following page.

Acura ARX-05

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.395
3200		1.395
3600		1.528
4000		1.639
4400		1.681
4800		1.732
5200		1.740
5600		1.749
6000		1.749
6200		1.739
6400		1.724
6600		1.724
6800		1.699
7050		1.668
7550		1.606
7650		1.000

Mazda RT24-P

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		2.091
5250		2.408
5750		2.425
6500		2.538
6750		2.546
7000		2.548
7250		2.551
7500		2.522
7750		2.465
8000		2.380
8250		2.318
8500		2.254
8750		2.216
9000		2.255
9800		2.000
9900		1.000







GTLM		Vehicles		Mass				Engine				Ride Height	Rear Wing		Fuel				Notes
Manufacturer		Minimum No Fuel/Driver (kg)		Restrictor Diameter (mm)		Average Power Delta (kW)	Maximum RPM	Minimum Ground Clearance (mm)	Min Angle (deg)	Gurney Minimum Height (mm)	Type	Minimum Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)				
		adj	current	qty.	adj.	current	adj	current	current	current	current	λ	adj	current					
BMW	M8 GTE		1230					7000	50.0	N/A	5.0	E20	1.08		90.0	34.0			
Corvette	C8R GTE		1290	1		44.3		7400	50.0	N/A	15.0	E20	0.88		98.0	34.0			
Porsche	911 RSR GTE		1275	2		32.2		9400	50.0	N/A	Integrated	E20	0.89		102.0	34.0			

**BMW M8 GTE**

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.230
2500		1.450
3000		1.970
3500		2.220
4000		2.230
4500		2.240
5000		2.110
5250		2.035
5500		1.960
5750		1.895
6000		1.830
6500		1.770
6750		1.640
7000		1.510
7500		1.255
7600		1.000





GTD		Vehicles		Mass		Engine				Ride Height		Fuel				Notes	
Manufacturer		Minimum No Fuel/Driver (kg)		Restrictor Diameter (mm)		Average Power Delta (kW)		Maximum RPM		Minimum Ground Clearance (mm)		Type	Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)	
		adj	current	qty.	adj	current	adj	adj	current	adj	current		λ	adj	current		
Acura	NSX GT3		1325						7500		50.0	IMSA 100	0.88		108.0	40.0	
Aston Martin	Vantage AMR GT3		1270						7200		50.0	IMSA 100	0.91		103.0	40.0	
Audi	R8 LMS GT3		1310	2		40.0			8500		50.0	IMSA 100	0.91		100.0	40.0	
BMW	M6 GT3		1325						7250		50.0	IMSA 100	0.92		107.0	40.0	
Ferrari	488 GT3	+10	1335						7500		50.0	IMSA 100	0.90		101.0	40.0	
Lamborghini	Huracan GT3		1340	2		39.0			8500		50.0	IMSA 100	0.89	-2.0	105.0	40.0	
Lexus	RC F GT3		1385	2		36.0			7200		50.0	IMSA 100	0.86		102.0	40.0	
Mercedes	AMG GT3		1380	2		34.5			7700		50.0	IMSA 100	0.90		106.0	40.0	
Porsche	911 GT3 R		1320	2		38.0			9500		50.0	IMSA 100	0.88		97.0	40.0	





Acura NSX GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.738
4000		1.738
4500		1.741
5000		1.788
5500		1.852
6000		1.906
6200		1.933
6300		1.943
6400		1.946
6500		1.944
6600		1.939
6700		1.929
6800		1.913
7000		1.881
7500		1.824
7800		1.000

Aston Martin AMR GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.491
4000		1.491
4250		1.530
4500		1.568
4750		1.617
5000		1.665
5250		1.699
5500		1.733
5750		1.772
6000		1.772
6250		1.772
6500		1.772
6750		1.743
7000		1.723
7200		1.723
7500		1.000

BMW M6 GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.551
3000		1.753
4000		1.877
4500		1.922
4750		1.960
5000		1.967
5250		1.947
5500		1.913
5750		1.855
6000		1.819
6250		1.785
6500		1.751
6750		1.670
7000		1.535
7250		1.464
7550		1.000

Ferrari 488 GT3

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.456
4000		1.456
4500		1.496
4750		1.521
5000		1.546
5250		1.565
5500		1.583
5750		1.584
6000		1.584
6250		1.574
6500		1.563
6750		1.540
7000		1.517
7250		1.473
7500		1.430
7800		1.000

