

IMSA TECHNICAL BULLETIN IWSC #22-13

To: All IMSA WeatherTech SportsCar Competitors
From: IMSA Competition
Date: March 9, 2022
Re: IMSA Mobil 1 Twelve Hours of Sebring Tables

One Daytona Blvd.
Daytona Beach, FL
32114
: +1 (386) 310-60

In accordance with Attachment 2 of the IMSA WeatherTech SportsCar Championship SSR, the following road course Balance of Performance values are set for the indicated Car Models. The column listed as current is the current specification after any adjustment is applied and thus the required specification for the Event. These decisions come into immediate effect and are applicable until further notice.



Technical Bulletin

DPI	Vehicles	Mass		Engine						Aero	Fuel				Notes			
Manufacturer		Minimum No Fuel/Driver (kg)		Make	Volume (L)	Turbo/NA	Restrictor Diameter (mm)			Average Power Delta (kW)	Maximum RPM	Configuration	Type	Declared Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)	
		adj	current				qty.	adj	current	adj					current	λ		
Acura	ARX-05		930	Acura	3.5	Turbo					7050	See Table	E20	0.89		78.0	30.0	
Cadillac	DPI-V.R		945	Cadillac	5.5	NA	2		32.2		7600	See Table	E20	0.90		71.5	30.0	

* Aero configuration is defined via the Aero Configuration table on the following page.

Acura ARX-05

Engine Speed	Boost Ratio	
	adj	current
[rpm]		
2000		1.395
3200		1.395
3600		1.528
4000		1.639
4400		1.681
4800		1.732
5200		1.740
5600		1.749
6000		1.749
6200		1.739
6400		1.724
6600		1.724
6800		1.699
7050		1.668
7550		1.606
7650		1.000

DPI		FRONT AERODYNAMIC CONFIGURATIONS			REAR AERODYNAMIC CONFIGURATIONS									
		Optional Front Aerodynamic Configurations are Independent			Optional Rear Aerodynamic Configurations Must be Used as a Complete Package; Mixing of Parts/Components is Forbidden									
DPI AERODYNAMIC CONFIGURATIONS		Dive Planes	Packers / Inserts	Other	Option	Tail Wicker		Rear Wing Assembly		Rear Wing Flap			Rear Wing Flap Wicker	
Manufacturer		Permitted Options	Permitted Configurations	Permitted Options		Type	Maximum Height	Type	Maximum Angle / Position	Type	Position	Maximum Angle	Span	Maximum Height
						mm	mm		degrees			degrees	mm	mm
Acura	ARX-05	Per Technical Credential [IMSA]:	Per Technical Credential [IMSA]:	Per Technical Credential [IMSA]:	OPTION 1	Per Technical Credential [IMSA]	Removed	Per Technical Credential [IMSA]	12.4	Sprint As-Homologated [FIA]	N/A	31.7	1800	10.0
		Lower	As-Tested [IMSA]	Acura Side Wicker			16.3 Per Template							
		Double		All Front Fender Wicker Options			28.3 Per Template							
Cadillac	DPI-V.R	Per Technical Credential [IMSA]:	Per Technical Credential [IMSA]:	Per Technical Credential [IMSA]:	OPTION 1	Per Technical Credential [IMSA]	Removed	Sprint As-Homologated [FIA]	15.0	Sprint As-Homologated [FIA]	Rotated	26.8	1200	5.0
		2019 HDF Lower	Splitter Outboard Fill-in Packers	Cadillac Side Wicker			8.0							
		2020 HDF Lower												
		Double	Front Wheel Arch Packer + Lateral Wicker	Must run Hood Opening at all times			30.0							
			Must run STD Front Fender Insert at all times	10mm Front Fender Wicker										

LMP2		Vehicles		Mass		Engine			Aero	Fuel			Notes
Constructor		Minimum No Fuel/Driver (kg)		Make	Volume (L)	Maximum RPM	Configuration	Type	Total Capacity (L)		Minimum Full Refueling Time (sec)		
		adj	current						adj	current			
Dallara	P217		940	Gibson	4.2	8700	See Table	E20		75.0	34.0		
Ligier Automotive	Ligier JS P217		940	Gibson	4.2	8700	See Table	E20		75.0	34.0		
ORECA	07		940	Gibson	4.2	8700	See Table	E20		75.0	34.0		

* Aero configuration is defined via the Aero Configuration table on the following table.

LMP2		FRONT AERODYNAMIC CONFIGURATIONS			REAR AERODYNAMIC CONFIGURATIONS									
LMP2 AERODYNAMIC CONFIGURATIONS		Optional Front Aerodynamic Configurations are Independent			Optional Rear Aerodynamic Configurations Must be Used as a Complete Package; Mixing of Parts/Components is Forbidden									
Constructor		Dive Planes	Packers / Inserts	Other	Option	Tail Wicker		Rear Wing Assembly		Rear Wing Flap			Rear Wing Flap Wicker	
		Permitted Options	Permitted Configurations	Permitted Options		Type	Maximum Height	Type	Maximum Angle / Position	Type	Position	Maximum Angle	Span	Maximum Height
						mm	mm		degrees			degrees	mm	mm
Dallara	P217	As-Homologated [FIA]: Lower Double	As-Homologated [FIA]	As-Homologated [FIA]	OPTION 1	Per Technical Credential [IMSA]	8.0	Per Technical Credential [IMSA]	16.0	Sprint As-Homologated [FIA]	STD	23.4	1200	5.0
Ligier Automotive	Ligier JS P217	As-Homologated [FIA]: MDF HDF	As-Homologated [FIA]	As-Homologated [FIA]	OPTION 1	As-Homologated [FIA]	12.5	Sprint As-Homologated [FIA]	15.3 (A1/MP1)	Sprint As-Homologated [FIA]	F4/0	N/A	N/A	
ORECA	07	As-Homologated [FIA]: Lower Double	As-Homologated [FIA]	As-Homologated [FIA]	OPTION 1	As-Homologated [FIA]	16.3	Sprint As-Homologated [FIA]	13.6 (Position 1)	Sprint As-Homologated [FIA]	N/A	33.5	Full	10.0

GTD		GTD PRO		Vehicles		Mass		Engine			Ride Height		Fuel				Notes
Manufacturer		Minimum No Fuel/Driver (kg)		Restrictor Diameter (mm)		Average Power Delta (kW)	Maximum RPM		Minimum Ground Clearance (mm)		Type	Lambda	Total Capacity (L)		Minimum Full Refueling Time (sec)		
		adj	current	qty.	adj	current	adj	adj	current	adj	current		λ	adj	current		
Acura	NSX GT3		1305					7500		50.0	IMSA 100	0.88		107.0	40.0	EVO II	
Aston Martin	Vantage AMR GT3		1270					7200		50.0	IMSA 100	0.91		106.0	40.0		
BMW	M4 GT3		1315					7000		50.0	IMSA 100	1.10		106.0	40.0		
Corvette	C8.R GTD		1340	1		41.0		7400		50.0	IMSA 100	0.88		88.0	40.0	15 mm Rear Wing Gurney Required, 40 kg in BoP Ballast Box (+/-3 kg)	
Ferrari	488 GT3		1335					7500		50.0	IMSA 100	0.90		101.0	40.0		
Lamborghini	Huracan GT3		1340	2		39.0		8500		50.0	IMSA 100	0.89		104.0	40.0		
Lexus	RC F GT3		1360	2		37.0		7200		50.0	IMSA 100	0.86		103.0	40.0		
McLaren	720S GT3		1295					8000		50.0	IMSA 100	0.88		104.0	40.0		
Mercedes	AMG GT3		1370	2		35.0		7700		50.0	IMSA 100	0.90		105.0	40.0		
Porsche	911 GT3 R		1320	2		38.0		9500		50.0	IMSA 100	0.88		96.0	40.0		



Technical Bulletin

Acura NSX GT3

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.838
4000		1.838
4500		1.842
5000		1.887
5500		1.915
6000		1.929
6200		1.933
6300		1.943
6400		1.946
6500		1.944
6600		1.939
6700		1.929
6800		1.913
7000		1.881
7500		1.824
7800		1.000

Aston Martin AMR GT3

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.491
4000		1.491
4250		1.530
4500		1.568
4750		1.617
5000		1.665
5250		1.699
5500		1.733
5750		1.772
6000		1.772
6250		1.772
6500		1.772
6750		1.743
7000		1.723
7200		1.723
7500		1.000

BMW M4 GT3

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		2.166
3000		2.166
3500		2.166
4000		2.224
4500		2.294
5000		2.387
5250		2.451
5500		2.533
5750		2.625
6000		2.645
6250		2.667
6500		2.583
6750		2.487
7000		2.340
7250		2.229
7500		1.000

Ferrari 488 GT3

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.456
4000		1.456
4500		1.496
4750		1.521
5000		1.546
5250		1.565
5500		1.583
5750		1.584
6000		1.584
6250		1.574
6500		1.563
6750		1.540
7000		1.517
7250		1.473
7500		1.430
7800		1.000

McLaren 720S GT3

Engine Speed [rpm]	Boost Ratio	
	adj	current
2000		1.616
4000		1.616
4500		1.610
5000		1.604
5500		1.598
5750		1.579
6000		1.561
6250		1.533
6500		1.505
6750		1.463
7000		1.421
7250		1.389
7500		1.356
7750		1.352
8000		1.347
8300		1.000