

4 October 2023

MMTB-IWSC-2023-21

Michelin Motorsport Technical Bulletin

IWSC GTP Tire usage requirements for Michelin Raceway Road Atlanta

Front 29/71-18 Nominal Rim : 12.5 (+0/- 0.5)x18		# stints Front Slick Tire 29/71-18 GTP - Michelin Raceway Road Atlanta 2023			
Camber \ Pressure		1.7 b = 24.7 psi	1.8 b = 26.1 psi	1.9 b = 27.6 psi	2 b = 29.0 psi
Max -3.50°		0	0	0	0
Max -3.25°		0	0	0	0
Max -3.00°		0	2	3	3
Max -2.75°		0	2	3	3
Max -2.50°		0	2	3	3
Max -2.25°		0	2	3	3
Max -2.00°		0	2	3	3
Max -1.75°		0	2	3	3
Min -1.00°		0	2	3	3
Rear 34/71-18 Nominal Rim : 14 (+0/- 0.5)x18		# stints Rear Slick Tire 34/71-18 GTP - Michelin Raceway Road Atlanta 2023			
Camber \ Pressure		1.7 b = 24.7 psi	1.8 b = 26.1 psi	1.9 b = 27.6 psi	2 b = 29.0 psi
Max -3.00°		0	0	0	0
Max -2.8°		0	0	0	0
Max -2.5°		0	0	0	0
Max -2.3°		0	2	3	3
Max -2.00°		0	2	3	3
Max -1.8°		0	3	2	3
Max -1.50°		0	3	2	3
Max -1.3°		0	3	2	3
Min -1.00°		0	3	2	3
<div>TPMS mandatory</div> <div>Stabilized Pressure = average pressure over one lap when pressure variation lap-to-lap is ≤ 2% during stint</div> <div>Recommended minimum cold pressure = Stabilized pressure -0.6b</div> <div>Recommended maximum stint length = 175km</div> <div>Minimum Static Pressure (for tire pressure control in pit box) = 1.7b</div>					
% best Lap Time Slick			138% - 114%		113% - 104% **
249D/449D		Wet	2 stints - 1.6 bar		1 stint - 1.6 bar
** if the car does one laptime ≤ this limit during the stint, tires should be changed at the end of this stint					

