



15 November 2023

MMTB-IMPC-2024-05

Michelin Motorsport Technical Bulletin

TCR Tire Usage Requirements - All tracks

**27/65-18**

S9M+					
Usage :		ALL TRACKS			
Max speed :		320 km/h			
Nominal Rim :		10 J 18			
Recommended Minimum cold pressure :		23.2 Psi / 1.6 bar			
Recommended Maximum Stint length :		200 km			
Number of stints	Stabilized pressure				
Camber	29.0 Psi 2.0 bar	30.5 Psi 2.1 bar	31.9 Psi 2.2 bar	33.4 Psi 2.3 bar	34.8 Psi 2.4 bar
More negative than -4.0°	0	0	0	0	0
-3.51° to -4.0°	0	0	1	2	2
From -2° to -3.5°	0	0	2	2	2

Negative camber beyond -4.0 degrees is prohibited.

Stabilized pressure in excess of 34.8 psi / 2.4 bar is permitted.

Stabilized Pressure = average pressure over one lap when pressure variation lap-to-lap is ≤ 1% during stint

For cars without IMSA TPMS - Stabilized Pressure = the pressure taken by gauge immediately upon pit box entry at end of a stint



# 27/65-18

P2L					
	Usage :	<b>ALL TRACKS</b>			
	Max speed :	<b>320 km/h</b>			
	Nominal Rim :	<b>10 J 18</b>			
	Recommended Minimum cold pressure :	<b>20.3 Psi / 1.4 bar</b>			
	Recommended maximum Stint length :	<b>200 km</b>			
Number of stints	Stabilized pressure				
Camber	26.1 Psi 1.8 bar	27.6 Psi 1.9 bar	29.0 Psi 2.0 bar	30.5 Psi 2.1 bar	31.9 Psi 2.2 bar
More negative than -4.0°	0	0	0	0	0
-3.51° to -4.0°	0	0	1	1	1
From -2° to -3.5°	0	0	1	1	1

Negative camber beyond -4.0 degrees is prohibited.

Stabilized pressure in excess of 31.9 psi / 2.2 bar is permitted.

Stabilized Pressure = average pressure over one lap when pressure variation lap-to-lap is ≤ 1% during stint

For cars without IMSA TPMS - Stabilized Pressure = the pressure taken by gauge immediately upon pit box entry at end of a stint